

Deutz 2011 Whispa Kits

Quiet, Lightweight, powerful, reliable and cost effective

Specifications.

Noise levels

F3L2011 3 cylinder diesel	Noise Levels @ 1500rpm	Noise Levels @ 2000rpm	Noise Levels @ 2300rpm	Noise Levels @ 2800rpm
dBa @ 1m	77.08	79.31	80.86	82.55
dBa @ 7m	65.43	70.35	69.53	71.28

BF4L2011 4-cylinder diesel/Turbo.	Noise Levels @ 1500rpm	Noise Levels @ 2000rpm	Noise Levels @ 2300rpm	Noise Levels @ 2800rpm
dBa @ 1m	78.82	82.21	84.43	88.59
dBa @ 7m	65.00	67.99	70.76	74.32

Dimensions

Model	Weight in kgs.	Length	Width	Hight
F3L2011 c/w whispa kit.	238	115cm	74cm	70cm
BF4L2011 c/w whispa kit.	334	130cm	100cm	74cm

Power Outputs

Model	Continuous Power output @ 1500rpm	Continuous Power output @ 2000rpm	Continuous Power output @ 2300rpm	Continuous Power output @ 2800rpm
F3L2011 c/w whispa kit.	18.7kw	25.8kw	29.3kw	34.0kw
BF4L2011 c/w whispa kit.	33kw	42.7kw	47.5kw	55.1kw

All power outputs are Com Tier 2 compliant up to 2800rpm.

Standard rating to ISO3026/1

The values/measurements given in this data sheet is for information purposes only and are not binding.

#The information given in the offer is decisive.

Deutz Australia Pty. Ltd. reserves to the right to make changes to specifications at any given moment without notification.

#Sound level measurements conform to AS1259.

DEUTZ®

Deutz Whispa Kits