

DPS 220 DG

TECHNICAL DATA SHEET

MAIN DATA

Prime power (PRP)	200.0 (kVA)
Prime power (PRP)	160.0 (kW)
Standby power (LTP)	220.0 (kVA)
Standby power (LTP)	176.0 (kW)
Voltage, Frequency, pf	415V, 50HZ @ 0.8
Sound pressure 7m dBA	73.0

ENGINE

Engine brand	DEUTZ
Engine model	BF6M1013FCG3
Cylinders	6
Speed	1500 rpm
Cubic capacity	7.15 L
Air intake	Turbocharged
Standard voltage	12Vdc
SAE	2-11.5
BMEP	2250 kPa
Cooling	Water
Flywheel P.R.P. Power	174.6 kW
Flywheel Standby Power	kW
Precision class	G3
Oil Quantity	20.0 L
Engine coolant capacity	9.8 L
Radiator standard	IM50
Heat from radiator	96.1 kW
Heat from exhaust	0.0 kW
Heat from radiation	20.0 kW
Exhaust temperature	530 deg C
Cooling air flow	192.00 m3/min
Combustion air flow	0.00 m3/min
Exhaust gas flow	35.20 m3/min
TA Luft	NA
TA Luft/2	NA
EPA	NA
Stage	Stage 2



ALTERNATOR

Alternator brand	Stamford
Alternator model	UC1274H
P.R.P. Power	200.0 kVA
L.T.P. Power	220.0 kVA
Connection	Series Star
Phases	3PH + N
Winding	12 terminals Winding 311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	SX460
Precision	1.5 +/- %

CONTROL SYSTEM

Control system brand	COMAP
Control system model	AMF 25
I/O expansion module (optional)	BI08-EFCP
Remote monitoring (optional)	GSM/GRPS
Comms. expansion module (optional)	RS232/RS485

FUEL CONSUMPTION

Fuel Cons. @ 100% (LTP)	56.0 l/h
Fuel Cons. @ 100% (PRP)	50.8 l/h
Fuel Cons. @ 75% (PRP)	37.7 l/h
Fuel Cons. @ 50% (PRP)	25.3 l/h
Fuel Cons. @ 25% (PRP)	13.1 l/h

DIMENSIONS & WEIGHT (ACOUSTIC CANOPY)

Length	3230 mm
Width	1140 mm
Height	2230 mm
Mass (Dry)	2460 kg

BASE FRAME (ACOUSTIC CANOPY)

Base frame model	G10
Standard bunded tank	360 litres
Optional bunded tank	1800 litres

DIMENSIONS & WEIGHT (OPEN FRAME)

Length	2600 mm
Width	1120 mm
Height	1910 mm
Mass (Dry)	2000 kg

BASE FRAME (OPEN FRAME)

Base frame model	G10-O
Standard bunded tank	360 litres
Optional bunded tank	1800 litres

REFERENCE CONDITIONS

Standard reference condition temp.	25deg C
Altitude	100 masl
Relative humidity	30%
Atmospheric pressure	100 kpa
Power factor	0.8 lag
Balanced load	Non-distortional

Fuel consumption is nominal and refers to specific weight 0.850kg/l.

Sound power levels refer to free field conditions: Installation site may influence the values.

Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment. Any optional and additional equipment / accessories can modify weight, dimensions and performance.

P.R.P. Prime Power-Continuous power at variable load

The power that a generator can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the manufacturer according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the manufacturer.

L.T.P. Limited-time running power-Limited power

The maximum power that a generator can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the manufacturer according to ISO8528-1. The number of hours per year is stated by the manufacturer. Overload is not permitted.

For more information please contact your local DEUTZ Power Solutions sales partner.

